

# Automotive Exhaust Monitor

## INDUS SMOKE METER MODEL OMS 103



### NEVER BEFORE IN INDIA

- ◆ High Quality Indian Product with latest technology
- ◆ Very Compact, small in size & light in weight
- ◆ Easy to carry & operate
- ◆ Cable free technology
- ◆ Features battery-based tachometer
- ◆ Conforms to the latest specs of the Ministry of Road Transport & Highways

#### SPECIFICATIONS

Principle of Operation	Attenuation of light beam
Geometry	Folded Geometry
Smoke Measuring Cell	215mm
Measurement	Smoke Density in HSU & K; RPM & Oil Temperature
Range	HSU : 0-99.9; K: 0 to ∞ RPM : 0-6000; Oil Temperature : 0-150 °C
Resolution	HSU : 0.1%; K: 0.01m <sup>-1</sup> RPM : 1 (for Piezo), 10 (for Battery); Oil Temperature : 1°C
Accuracy	Opacity K : ±0.1m <sup>-1</sup> ; RPM : ±20 (Abs) or ±2% (Rel); Oil Temperature : ±2°C
Light Source & Detector	LED & Photocell
Display	16 x 2 Alphanumeric LCD Display with backlight
Keypad	Membrane Keypad , 18 keys, for user friendly operation
Warm-up Time	<20 minutes (Smoke Column Heating); Electronics (< 2min)
Time Constant	Physical : 0.4 sec; Electrical : 1msec
Temperature Sensor	RTD (PT100) & Thermocouple
RPM Sensor	Battery Based Tachometer (Standard), Piezo Sensor (Optional)
Data Communication	RS232 interface for computer connectivity
Printer (Optional)	24-column dot matrix printer, paper width 56 mm
Sampling Probe	3 probes of different diameters along with synthetic rubber hose of length 4m
Calibration	Using calibration filter of known K, Autocal system for mid-point check
Operating Temperature	0-50°C
Measuring Chamber Temperature	80°C
Power Supply	90- 270 V AC/ 11- 12 V DC
Dimension	450 x 200 x 140 mm
Weight	8 Kg



Manufactured & Marketed by :

**INDUS Scientific Private Limited**

11/2B, Hennur Bande, Hennur Road, Bangalore 560 043

T/F: (080) 2544 9762/ 64, Fax: + 91 80 2543 0914

Email: info@indusscientific.com

Website: www.indusscientific.com



ISPL-SM-002 Rev. 1.0 Date : 01-08-2008